



MISSE-16 Overview

4th VOLTRON Meeting, February 22-24, 2023

Elena Plis
Senior Research Engineer
elena.plis@gtri.gatech.edu

The views expressed are those of the author and do not necessarily reflect the official policy or position of the Department of the Air Force, the Department of Defense, or the U.S. government. The appearance of external hyperlinks does not constitute an endorsement by the United States Department of Defense (DoD) of the linked websites, or the information, products, or services contained therein. The DoD does not exercise any editorial, security, or other control over the information you may find at these locations.

Trade names and trademarks are used in this report for identification only. Their usage does not constitute an official endorsement, either expressed or implied, by the National Aeronautics and Space Administration.

Approved for public release; distribution is unlimited. Public Affairs release approval #

Team

- **Miles T. Bengtson**

Air Force Research Laboratory, Kirtland AFB, presently at Aurora Engineering

- **Ryan C. Hoffmann and Alexey Sokolovskiy**

Air Force Research Laboratory, Kirtland AFB

- **Daniel P. Engelhart**

University of New Mexico

- **Gregory P. Badura**

Georgia Tech Research Institute

- **Heather M. Cowardin**

NASA Orbital Debris Program Office

- **Jacqueline A. Reyes**

University of Texas at El Paso, presently at MIT Lincoln Laboratory


- **Timothy R. Scott**

DuPont de Nemours

- **Jainisha R. Shah and Sydney E. J. Collman**

Assurance Technology Corporation

Timeline




Motivation

Thorough characterization of physical and chemical changes of heritage and novel spacecraft materials under true space exposure and ground-based space-simulated weather is important

- Establishing correlation factors between true space exposure and accelerate space weather experiments
- Enabling accurate prediction of on-orbit material performance based on laboratory-based testing
- Supporting material identification for space situational awareness

Materials International Space Station Experiment (MISSE) Flight Facility (MISSE-FF) is a perfect testbed to generate benchmark data for the efficiency validation of ground-based space weather simulation experiments


Approach



Materials International Space Station Experiment (MISSE)

MISSE-16 Overview

- Samples on ram, wake, zenith faces
- Unique damage occurs on each face
- White and IR LEDs illuminate samples
- Camera records RGB and IR color data
- Comparison of orbital data with ground tests allows identification of damage pathways



ISS images by courtesy of www.nasa.gov

Approved for public release; distribution is unlimited. Public Affairs release approval #

UNCLASSIFIED

Orbital Experiment Measurement Cadence

MISSE-16 Mission Duration

| M1 | | | | | | | | | | | M2 | | | | M3 | M4 | M5 | M6 |
|--------|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|----|
| W1 | | | | | | | | W2 | W3 | W4 | W1 | W2 | W3 | W4 | | | | |
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | | | | | | | | | | | |
| Ram | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ |
| Wake | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ |
| Zenith | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ | ★ |

August 2022

Sept 2022

Oct 2022

Nov 2022

Dec 2022

Jan 2023

Exposure on January 18th

Wake: 143 days

Zenith: 156 days


Ram: 133 days

MISSE-16 Materials


| | Material | Type | |
|----|-------------------------------|----------------|---|
| 1 | Kapton® CR | PI/ PMDA | Corona-resistant; shielding of sensitive equipment |
| 2 | Kapton® CS | | Thermoformable; component of next-gen space solar cells |
| 3 | Kapton® WS | | High thermal stability; alternative for traditional PI film in MLI blankets |
| 4 | Kapton® XC | | Electrically conductive; space charge mitigation |
| 5 | Kapton® TF | | Thermoformable; candidate for small satellite parts manufacturing |
| 6 | DR9 | | Novel material in PI family |
| 7 | Kapton® HN | | “Golden standard” of space industry |
| 8 | Economyplate™ Carbon Fiber | CFRP | Used in construction of present-day LEO satellites |
| 9 | G-10/FR4 Glass Epoxy | GFRP | |
| 10 | Zenite® | LCP | Flexible LCP antennas and LCP-based circuits molded to available spacecraft areas |
| 11 | Melinex® 454 | PET | Candidates for improved MLI reflectivity and durability |
| 12 | Mylar® M021 | | |
| 13 | CORIN®XLS | POSS | Optical signature characterization for orbital debris and operational RSO |
| 14 | Thermalbright®N | | |
| 15 | Alumina | Alum. Oxide | Optical standard |

MISSE-16 Materials

Mount



Swing

Powered Hinge
Drive AssemblyUnderdeck
Volume

Photo/image credit: Aegis Aerospace





Image credit: NASA/JSC

MISSE-FF Camera Board Integration




Lights



Camera

Photo credit: AFRL




<https://www.baslerweb.com/en/products/cameras/area-scan-cameras/aca/aca2440-20gc/>

Basler daA1600-60uc camera with IR LED illumination that provides broad illumination ranges in IR region

MISSE-FF Camera Board Integration



Camera board assembly



Sample image delivered by the
Basler daA1600 camera

Image credit: AFRL

MISSE-16 Launch and MSC Installation



Photo credit: NASA

MISSE-16 Science Carriers (MSCs) were installed on the MISSE-FF on 31 July - 2 August 2022 with support from the Canada Space Agency ISS Robotic Systems Team





Photo credit: NASA


News Articles

Launch <https://spacenews.com/spacex-launches-cargo-dragon-mission-to-iss/>

Docking <https://spaceflightnow.com/2022/07/16/spacex-crs-25-iss-docking/>

Approved for public release; distribution is unlimited. Public Affairs release approval #

Representative Orbital Data (Visible)




Visible images of Kapton® CS on Ram, Zenith, and Wake ISS faces

Photo/image credit: Aegis Aerospace

Approved for public release; distribution is unlimited. Public Affairs release approval #

Representative Orbital Data (IR)




IR images of Kapton® CS on Ram, Zenith, and Wake ISS faces

Photo/image credit: Aegis Aerospace

Approved for public release; distribution is unlimited. Public Affairs release approval #

Spectral Analysis of MISSE-16 Flight Samples

Machine Learning Approach




- The ML Algorithm gives an estimated reflectance spectrum for each taken image
- Spectral characterization from a camera is an under-constrained problem since it involves mapping from a low dimensional space (RGB/IR pixel counts) to a high dimensional space (reflectance as a function of wavelength)
- Utilized ML approach uses a radial basis function (RBF) network

Approved for public release; distribution is unlimited. Public Affairs release approval #



Model Validation

- Model was trained on 140 samples of color ($L^*a^*b^*$ and IR) and spectral information
- Validation was done on approximately 70 samples of color ($L^*a^*b^*$ and IR) and spectral information. There was a 2/1 split in the training and validation datasets respectively
- Dark lines represent mean reconstruction error and transparent bars represent the spread of the error
- Model is able to retrieve the spectrum to within 10% error for the majority of samples across wavelengths 350nm to 900nm
- Lowest overall error is near the green (500nm) and red (650nm) wavelength regions and highest overall error occur in the blue (400nm) region.



- Data were preprocessed using empirical line method alignment for white balancing prior to feeding it to the ML model

KaptonCS



Reflectance curves extracted from the visible RAM images of Kapton® CS

Material Characterization of MISSE-16 Flight Duplicate Samples

Weathering Facilities

Electron and VUV Exposure





Image credit: AFRL

- Materials may be irradiated with high-energy electrons (up to 100 keV) and/or exposed to VUV particles
- *In situ* directional hemispherical reflectance (DHR), surface potential decay (SPD), and Fourier-Transform Infrared (FTRI) spectral measurements capabilities

AO Exposure



U.S. Patent 4,894,511, Foreign Patent
Image credit: PSI

- Targeted peak fluence of 2×10^{20} O/cm²
- 8 km/s O-atom beam generated in high vacuum chamber with pulsed laser discharge
- AO beam is a neutral atom beam with a ~1% O⁺ ion content

Characterization Measurements

| Material | | Characterization Technique/Responsible Party | | | | | | | | | | |
|----------|-----------------|--|-----|-----|----------------------|-----|------|------|-----|------------------|-----|---------------|
| | | Surface morphology | | | Optical measurements | | | | | Charge Transport | | Vis/IR camera |
| | | DSLIR | SEM | AFM | R % | T % | BRDF | FTIR | DHR | ASTM | SPD | Images |
| 1 | Kapton® CR | | | | | | | | | | | |
| 2 | Kapton® CS | | | | | | | | | | | |
| 3 | Kapton® WS | | | | | | | | | | | |
| 4 | Kapton® XC | | | | | | | | | | | |
| 5 | Kapton® TF | | | | | | | | | | | |
| 6 | Kapton® HN | | | | | | | | | | | |
| 7 | DR9 | | | | | | | | | | | |
| 8 | CFRP | | | | | | | | | | | |
| 9 | GFRP | | | | | | | | | | | |
| 10 | Zenite® | | | | | | | | | | | |
| 11 | Melinex® 454 | | | | | | | | | | | |
| 12 | Mylar® MO21 | | | | | | | | | | | |
| 13 | CORIN®XLS | | | | | | | | | | | |
| 14 | Thermalbright®N | | | | | | | | | | | |



NASA JSC




GTRI




SCICL (AFRL)

Characterization Measurements



- Single-layer films were prepared and characterized
- AFM measurements were repeated at least 5 times per sample
- Measurements were often repeated for verification

Representative Characterization Results



Material's representative characterization portfolio of Mylar M021

Summary and Future Work

In the project's framework:

- Finish analysis of orbital images
- Subject flown materials to the same characterization protocol as flight-duplicates
- Compare results obtained from the flight duplicates and flown materials
- Make findings available to the research community

Future projects:

- Expand characterization portfolio to mechanical and chemical analysis
- Work with ISS NL to launch the mechanical testing experiment
- Organize all the measured data into the database
- Investigate combined exposure approach (e/VUV, e/VUV/AO, e/T, VUV/T..)
- Expand to different material types, such as Kevlar or PEDOT
- Broaden our collaborative network

Thank you!